



Indumaster® Radical IR 40

Alkaline industrial cleaner



Area of application

- For use in the industrial and workshop sector
- For all alkali-resistant floors and surfaces

Product properties

- Universally applicable
- Powerful dirt-removing capacity
- Cleans industrial oils and greases in particular
- Low-foaming
- Quick separation according to ÖNORM B 5105
- Suitable for application in cleaning machines, single-disc machines and high-pressure cleaning equipment

Application and dosage

- Always use cold water.
- Rinse with clean water.
- Consumption: 0,12 - 2,5 ml / per m²



100 ml /
10 l water



500 - 1.000 ml
/ 10 l water




100 - 500 ml
/ 10 l water



1:5 - 1:10
with water



- Apply fresh application solutions and consume them within 24 hours at the latest.



Note

- When used in the machine, the tanks should be cleaned and rinsed regularly.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

- **Product colour:** yellow
- **GISBAU code:** GG 80
- **UFI code:** UQ60-N0NJ-K00V-ECJE
- For professional use only.

Sales units

- IR40-0010RA: 1 x 10 l canister
- IR40-0200RA : 1 x 200 l Drum

Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.