




INDUMASTER® OFFENSIVE IR 47

Intensive industrial cleaner, highly alkaline



Fields of application

- For use in workshops and industrial applications
- Alkali-resistant floors and surfaces
- Epoxy resin coverings
- Tiles
- Ceramic and screed flooring

Product advantages/properties

- Breaks down dirt
- Dissolves the stubbornest of encrustations
- Removes heavy rust, oily and greasy soil
- High dispersing properties
- Foam-inhibited
- Suitable for use with cleaner machine or with high-pressure cleaning machine

| Technical data | |
|----------------|---------------|
| pH-Value | 13,5 |
| Product colour | yellow-orange |
| Container* | 10 l canister |

* Please note: Some products may not be available in all territories. Please talk to your customer service representative.





INDUSTRIAL CLEANER

Intensive cleaner

INDUMASTER® OFFENSIVE IR 47

Intensive industrial cleaner, highly alkaline

Application and dosage



Daily routine cleaning:
100 ml / 10 l water



Intensive cleaning:
500 ml / 10 l water



Machine cleaning:
100 ml / 10 l water



Basic cleaning:
1000 ml / 10 l water



High-pressure cleaning:
1:5 to 1:10 with water

Note

Always use cold water.

Do not mix with other cleaning agents. When being used in the auto-mat, the tanks should be regularly cleaned and rinsed.

Complementary products

Indumaster® Forte IR 42 - Solvent-based industrial and sports hall floor cleaner

Perfekt G 440 - Alkaline intensive cleaner

Multi Clean G 430 - Alkaline active cleaner

Indumaster® Fast IR 14 - Quick-drying machine cleaner, highly alkaline

Indumaster® Universal IR 55 - Ecological industrial cleaner

Indumaster® Step IR 16 - Neutral and material-compatible industrial cleaner

Indumaster® Protect IR 30 - Machine cleaner

Indumaster® Intensive IR 44 - Kitchen-industrial cleaner, phosphate-free

Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

For further safety precautions, please refer to the safety data sheet for Indumaster® Offensive IR 47 at www.buzil.com.

GISBAU-Code: GG 90

Article number*:
IR47-0010R1

* Please note: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

Date 05.12.2017

BUZIL-WERK Wagner GmbH & Co. KG

Fraunhoferstraße 17 . D-87700 Memmingen T +49 8331 930-6 . F +49 8331 930-880 . E-mail: info@buzil.de . www.buzil.com