

Corridor® + Protect Glossy

P 938

Ecological dispersion, glossy



EU Ecolabel:
{TXT_EU_

Area of application

- Ideal for use in healthcare facilities such as hospitals, nursing homes and doctor's offices as well as other areas where disinfectants are used
- For all water-resistant, coatable (including residual moisture) and thoroughly cleaned floor coverings such as PVC and linoleum
- Coatable PUR-modified coverings
- Also suitable for absorbent natural and artificial stone floors

Product properties

- Eco-certified, awarded the Austrian Ecolabel
- Durable, high-gloss polymer dispersion
- Resistant environmentally friendly formulation
- Very good filling power and good flow properties
- Forms a dirt-repellent and abrasion-resistant care film
- Facilitates maintenance cleaning through higher surface performance
- Free of metal salt
- Optimal alcohol and disinfectant resistance
- Slip-resistant according to DIN 51131
- Can be easily polished with the high-speed machine
- Economical, as it is suitable for dry care film restoration and for cleaning (spray method)
- Easily removable with Corridor®+ Multi Stripper P 937

Application and dosage

- Apply neat in 2 - 3 coats evenly on a thoroughly cleaned, neutralised and dry floor covering.
- Correct dosage saves costs and protects the environment.
- Apply undiluted a thin layer in 2 – 3 layers.
- Each layer must dry out on its own.
- Consumption: 25 - 35 ml / per m² / per order



undiluted



1:2 with water

8,5

pH 0 2 4 6 8 10 12 14



Note

- Protect from frost.
- Avoid direct sunlight.
- Before processing, turn off heat sources (underfloor heating, heating, hot supply air).
- A single, temporary exposure on the surface without mechanics, to commercially available disinfectants (max. 15 Minutes of continuous stress) is tested and does not cause any damage to the coating surface.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

- **Product colour:** white
- **Austrian Ecolabel:** UW 1126
- **GISBAU code:** GE 10
- **UFI code:** QPT0-H069-9007-MTAP

Sales units

- P938-0005: 1 x 5 l canister

Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.