

Method card

BUZIL-WERK Wagner GmbH & Co. KG

MARADIN HC 43

Application area: Surface



pH 10

Dilution	10 - 40 ml / 10 l water		
Suitable for	Intensive cleaning in: Buildings; Sport floors (DIN 18032/2); Workshops	Not suitable for	Textile surfaces
Application	Solvent sensitive surfaces / floors; Glass; Flexible floor coverings; Plastic; Concrete; Epoxy; Acrylic glass; Porcelain stoneware tiles		
 Trouble Shooting Before initial use: Test material compatibility!	Issue / Failure / Requirement <ul style="list-style-type: none"> ▪ Leaves streaks / film on surface / too much foam in dilution ▪ Low / weak cleaning effect ▪ No cleaning effect ▪ Damage on surface (discoloration, material swelling, etc.) ▪ Grey / mat appearance of surface due to hard water 	Solving Issue <ul style="list-style-type: none"> ▪ Adjust product dilution; rinse with clear water ▪ Select stronger cleaner i.e. Indumaster® Step IR 16, Indumaster® Intensive IR 44, Indumaster® Offensive IR 47 ▪ Select problem solver i.e. Indumaster® Forte IR 42 ▪ Check material's chemical & water resistance ▪ Clean periodically with O Tens Azid G 501 	

Method card

BUZIL-WERK Wagner GmbH & Co. KG

ALTERNATIVE PRODUCT | MARADIN HC 43

Application area:
Surface



pH 10

Alternative Product	Differentiation	Application
Indumaster® Step IR 16	pH 8,5, suitable for acrylic glass	Intensive cleaning / degreasing
Indumaster® Universal IR 55	Fast separating acc. ÖNORM B 5105	Ecological intensive cleaning / degreasing
Aktiv G 433	Standard intensive cleaner	Intensive cleaning / degreasing
Planta® Orange P 311	Ecological intensive cleaner	Intensive cleaning / degreasing